

Microcom 485TC Ticket Printer

Industrial quality ticket, tag, and label
thermal printer




**Batch printing so fast,
You're going to need extra seating.**

Microcom is proud to offer the first ticketing printer on the market with a full color touchscreen display. The touchscreen provides your box office with a user-friendly interface that gives you the ability to change printer settings "on the fly" and grants flexibility in between print jobs that may sporadically arise. The touchscreen is a standard feature on any 485 desktop printer.

Touchscreen Key Features include:

- 3" touchscreen display
- High resolution RGB color
- Configurable settings
- Real time status monitoring



www.houseoftickets.com.au

Hassle-free Ticketing Printer

The 485TC is an industrial quality thermal ticket printer capable of handling any box-office application. From single ticket to large batch printing, this model easily manages any job thrown its way. It's compatible with most ticketing software on the market making the integration process simple for the user. The printer can print on various styles (continuous and fanfold paper up to .013" thick) and widths of tickets (from 1.5" to 4.375") so there's no need to change existing ticket stock.

More Features for Less

Microcom's 485TC comes standard with a long list of features such as Ethernet, touchscreen display, and adjustable black line sensors. Additionally, the printer boasts the largest flash memory on the market of up to 512MB for downloading graphics and scalable fonts. Batch printing is now even faster with a print speed up to 8" per second. Combine these with our optional features to create an affordable, reliable printer that can stand the test of time.

Application Overview:

- Live Event Ticketing
- Admissions Processing
- Box-Office
- Voucher Issue
- Transportation
- Parking

Microcom 485TC (Compact) Ticket Printer



Performance Summary ◆◆◆

- 203 or 300 dpi resolution
- Up to 8" (200 mm) per second print speed
- Auto loading capability
- Microsoft Windows® driver
- Emulation: FGL
- Adjustable black line sensor configurable to sense left or right edge, bottom or top of media
- Industrial cabinet
- 3" touchscreen display
- Serial, USB, and Ethernet interface
- Optional high reliability rotary cutter
- Host USB port for offline code updates
- Software controlled print contrast adjustment
- Self-centering and locking media guides

Bar Codes ◆◆◆

- Code 39
- Codabar
- Interleaved 2 of 5
- Aztec
- EAN13
- EAN8
- UPC
- Softstrip
- Code 128
- PDF-417
- GS1 DataMatrix (ECC 200)
- QR
- And many more

Fonts ◆◆◆

- 16 Resident fonts including OCR-A and OCR-B
- Downloadable scalable fonts
- All fonts expandable in height and width
- 0, 90, 180 and 270 degrees font and bar code printing

Printing ◆◆◆

- Direct thermal, on-demand label/ticket and batch mode printing
- Paper width: 1.5" - 4.375" (38.1 mm-111 mm)
- Print width: up to 4.26" (108.2 mm)
- Paper thickness: up to .013" (.33 mm)
- Prints on continuous roll, fan-folded paper, and event tickets

Memory ◆◆◆

- Up to 512MB Flash
- Up to 256MB RAM

Physical Dimensions ◆◆◆

Height	Width	Depth	Weight
7.4" (188 mm)	8.1" (205 mm)	5.8" (148 mm)	10.3 lbs. (4.7 kg)

Environmental Conditions ◆◆◆

- Relative humidity: 10-85% non-condensing
- Operation temperature: 40° F to 104° F (5° C to 40° C)
- Power supply: Internal supply with auto-sensing; 90-264 VAC, 3.5/1.5 A, 47-63 Hz

Compliance ◆◆◆

- RoHS
- FCC Class A
- cTUVus

Warranty ◆◆◆

- One year limited warranty

Microcom 485TC Optional Features

- Industrial Quality Rotary Cutter
- Supply Roll Holder
- Catch Tray



Available from:

HOUSE OF TICKETS PTY LTD
PO Box 1611
Bowral NSW 2576
p. 02 4862 3733
www.houseoftickets.com.au

This product is RoHS compliant.



© Copyright 2020 Microcom Corporation. All rights reserved.

Microcom Corporation reserves the right to make improvements to their products at any time without prior notice. The information contained herein is subject to change without notice. Microcom Corporation shall not be liable for technical or editorial omissions contained herein. Reproduction, adaptation or translation without prior written permission is prohibited, except as allowed under the copyright laws. All company and product names are trademarks or registered trademarks of their respective owner.

830032-0006